

(12) UK Patent Application (19) GB (11) 2 165 559 A

(43) Application published 16 Apr 1986

(21) Application No 8522443

(22) Date of filing 10 Sep 1985

(30) Priority data

(31) 8422863

(32) 11 Sep 1984

(33) GB

(71) Applicant
University College London (United Kingdom),
Gower Street, London WC1E 6BT

(72) Inventors
Timothy Noel Mills,
Christopher Paul Swain

(74) Agent and/or Address for Service
Elkington and Fife, High Holborn House, 52/54 High
Holborn, London WC1V 6SH

(51) INT CL⁴
D05B 23/00 A61B 17/04

(52) Domestic classification
D1G AA F MA
A5R EW
B4C 104 A2 B7 B9
U1S 1027 1067 B4C

(56) Documents cited
GB A 2085934
GB A 2050448
GB 0461673
US 4484580

(58) Field of search
D1G

(54) Sewing or stapling machine

(57) A sewing machine for forming stitches in a substrate (16, 116), for example in forming stitches in tissue during surgery, comprises a needle (6; 106; 20, 30) for passing thread (9, 109, 24) into the substrate from one side thereof at a first location and for withdrawing the thread from the substrate at a second location spaced from the first location. The needle is removably operable solely from the said one side of the substrate. A stapling machine is also disclosed operating on similar principles for similar purposes.




Fig.1a

2165559




Fig.1a




Fig.1b




Fig.1c

2165559

2/7




Fig. 2




Fig. 3a




Fig. 3b

2165559

3/7




Fig. 4a




Fig. 4b




Fig. 4c






Fig. 4d



2165559

4/7




Fig. 4e




Fig. 4f




Fig. 4g






Fig. 4h



2165559

5/7




Fig.5a




Fig.5b




Fig.5c

2165559

6/7




Fig. 6a




Fig. 6b




Fig. 6c




Fig. 6d




Fig. 6e




Fig. 6f

2165559

7/7




Fig. 7a




Fig. 7b




Fig. 7c

1

GB 2 165 559 A

1

SPECIFICATION

Sewing or stapling machine

5 This invention relates to sewing machines and stapling machines. The invention has particular application to sewing required in surgical procedures, and, more particularly, relates to sewing and stapling machines which can be used inside the body
10 of a patient without the need to make an internal incision in the patient, the machine being controlled externally of the patient, for example by endoscopic means. For convenience such a machine is referred to below as an endoscopic sewing or
15 stapling machine, and the ensuing description relates largely to endoscopic sewing and stapling machines. It is to be understood, however, that sewing and stapling machines according to the present invention could be used in other applications.

20 According to one aspect of the present invention there is provided a sewing machine for forming stitches in a substrate, comprising means for passing a thread into the substrate from one side thereof at a first location and for withdrawing the
25 thread from the substrate at a second location spaced from the first location, the said means being remotely operable solely from the said one side of the substrate.

30 According to another aspect of the invention there is provided a stapling machine operating on similar principles. The machines according to the present invention open up the possibility of performing a wide range of internal surgical procedures without having to make an external incision
35 in the patient. Potential medical uses of such machines could include the oversewing of bleeding or perforated ulcers, the oversewing of bleeding varices, the narrowing of lax internal anatomical
40 sphincters or organs, the closure of internal holes or fistulae, the assistance in the removal of normal or abnormal tissue, and the attachment of materials or objects to the walls of tissue (for example for attaching gastric tubes for feeding purposes to
45 the wall of the stomach, or for attaching X-ray opaque markers to mark the site of, say, a cancer, or for attaching a piece of material containing a drug to permit localised internal treatment).

50 *Figures 1a, 1b, and 1c* show a first embodiment of a sewing machine according to the present invention, in three successive stages of operation;

Figure 2 shows, by way of example, one stitch pattern which can be formed by the machine of *Figures 1a to 1c*;

55 *Figures 3a and 3b* are underplan and side elevational views respectively showing a second embodiment of a sewing machine;

60 *Figures 4a to 4h* show diagrammatically the second embodiment of sewing machine in successive stages of operation, each Figure comprising two longitudinal sections through mutually perpendicular planes, in order to enable the operation of the machine to be more easily visualised in three dimensions, one of the longitudinal sections in each
65 Figure being taken along the section line indicated

in the other;

70 *Figures 5a to 5c* show longitudinal sections through an embodiment of stapling machine according to the present invention, in successive stages of operation;

Figures 6a to 6f show a third embodiment of the present invention in successive stages of operation; and

75 *Figures 7a to 7c* are, respectively, a plan view, a vertical section and an end view of a thread guillotine for use in conjunction with the sewing machine of the present invention.

80 The embodiment shown in *Figures 1a to 1c* comprises a block 1 preferably formed of a transparent material such as perspex. A slot 2 is formed in the block 1, the slot extending from the front to the back of the block, i.e. in a direction perpendicular to the plane of the paper. The block also has two longitudinal channels 3 and 4 formed therein. The
85 channel 3 receives a needle 5 which is longitudinally slidable in the channel 3 under the control of a control wire 6. The needle 6 has a head portion 7 in which is formed an eye 8, and a thread 9 to be used in sewing is passed through the eye 8. The channels 3 and 4 are continuous with corresponding channels 17 and 18 formed in a two-channel
90 endoscope tube 19.

95 The block 1 also has a compartment 10 formed therein, distal to the slot 2. A shoe 11 is pivotally mounted in the compartment 10 about a pin 12. The rear portion 13 of the shoe 11 is resilient and serves to bias the shoe in an anti-clockwise direction into the position shown in *Figure 1a*. A hook 14 is mounted for pivotal movement on the pin 12.
100 The hook 14 is approximately in the shape of a V, and a control wire 15, which passes down the channels 4 and 18, is attached to the hook 14 adjacent the vertex of the V. A source of suction (not shown) is connected to the proximal end of channel 18 for a purpose which will be described below.

105 Turning now to the operation of the machine, the initial position is shown in *Figure 1a*, with the machine positioned above a layer of tissue 16 in which it is desired to form stitches. Suction is then applied to the slot 2 to suck into the slot a double layer of tissue, as can be seen in *Figure 1b*. The depth of the slot 2 controls the amount of tissue which is sucked in. The needle 5 is then forced forwards through the double layer of tissue, as is also shown in *Figure 1b*. The needle carries with it the loop of thread 9. The tip of the needle strikes the shoe 11 which is thereby caused to pivot downwards against the biasing force of the shoe portion 13. The control wire 15 is then pulled
120 rightwardly to cause the hook 14 to pivot and thereby catch the loop of thread carried by the eye 8 of the needle 5. This can also be seen in *Figure 1b*. It should be mentioned at this point that the side of the head portion 7 of the needle has a groove (not shown) formed therein to allow the hook 14 to pass between the head portion 7 and the thread carried thereby.

125 As shown in *Figure 1c* the needle is then withdrawn leaving the loop of thread held between the
130

2 GB 2 165 559 A

2

hook 14 and the shoe 11. The suction applied to the slot 2 is then released and the double layer of tissue leaves the slot. This is also shown in Figure 1c, from which it can be seen that the effect of the steps described above is to pass a loop of thread from one side of the tissue through the tissue at a first location and back out of the tissue on the same side at a second location from the first location. As will be appreciated, this has been done without requiring access to the opposite side of the tissue which one would expect to be inaccessible under normal circumstances.

The machine is then moved to the site of the next stitch, suction is re-applied and the needle passes through a double layer of tissue at a different point. It is possible to form a variety of different stitches using the machine, but one example is shown diagrammatically in Figure 2. This stitch pattern is formed by moving the machine between successive stitches in a direction perpendicular to the plane of the paper in the drawings of Figure 1a to 1c. Figure 2 is a view taken looking down on the upper surface of the tissue shown in Figures 1a to 1c, and it will be seen that each of the loops formed by the hook 14 and the shoe 11 passes through the preceding such loop. How this is achieved can be understood by imagining the effect of moving the needle forwardly from the position shown in Figure 1c, with suction re-applied to the slot 2 to suck the tissue into the slot. It will be appreciated that the forward end of the needle will pass through the loop of thread caught between the hook 14 and the shoe 11, carrying a new loop of thread with it. It should be mentioned that to assist this process a small groove can be formed in the upper surface of the shoe, up which the tip of the needle can slide. This enables the needle to pass under the loop of thread already caught between the hook and shoe, without the risk that the needle may simply push the existing loop further up the surface of the shoe. Once the needle has placed the second loop through the first loop the hook 14 is pivoted to allow the first loop to be cast off by pulling on the tail of the thread. The hook 14 is then pivoted downwardly again, so that when the needle is withdrawn the second loop of thread is caught thereby.

As already mentioned, the body 1 is preferably made of a transparent material, so as to make it easier for the operator to see, and hence control, the operation of the machine. The control mechanisms can pass down the channel of an existing endoscope, or the machine can be used independently with a small supervising endoscope passed in parallel with the control channel of the machine.

The embodiment shown in Figures 3a and 3b is modular in construction, and comprises modules A to G joined face to face and held in position by suitable means, for example, a pair of longitudinally extending bolts passing through aligned bores in the individual modules. In the embodiment illustrated the modules B and D are formed of a transparent material and the remaining modules are not, but others of the modules may be transparent, and indeed it is preferable for some pur-

poses that at least the module A should be transparent.

The module A is the main body portion, and defines longitudinal channels 103 and 104, corresponding to the channels 3 and 4 shown in Figure 1. The channel 103 receives a needle 105, which is longitudinally slidable therein under the control of a control wire 108. The needle 106 has a head portion in which is formed an eye 108 and a thread to be used in sewing is passed through the eye. The channels 103 and 104 are continuous with corresponding channels 117 and 118 formed in a two-channel endoscope tube, the rest of the endoscope being omitted for simplicity in Figures 3a and 3b.

The module B has a slot 102 formed therein, which, as viewed in underplan view, extends across the central region of the module B and which, as viewed in elevation, extends from the top of the module to a location falling just short of the bottom.

The module B is separated by module C, which constitutes a spacer disc and which has an aperture 150 therein through which the needle 105 can pass, from the module D. Module D has a compartment 110 therein which is aligned with slot 102 in module B.

Modules E and F retain a pin 112 on which a U-shaped member 111 is pivotally mounted. The arms of the member 111 each carry a respective resilient wire 151. As can be seen in Figure 3, the wires converge towards one another at their tips as viewed in underplan, and, as can be seen in Figure 3b, the tip portions of the wires are bent upwards and one of the wires is longer than the other and thus extends further upwards than does the other.

A control wire 115, which passes down the channels 118 and 104 is attached to an arm 152 which is, in turn, rigidly connected to the U-shaped member 111.

The module G provides a curved or bevelled front end to the device, so as to increase the ease with which it can be introduced into a patient.

A source of suction (not shown) is connected to the proximal end of the channel 118 for a purpose which will be described in more detail below and which is basically similar to that for which the source of suction is used in the embodiment of Figure 1.

The operation of the device of Figures 3a and 3b will now be described with reference to Figures 4a to 4h. It should be noted that these figures are diagrammatic in character. In each case module G has been omitted, and the modular construction of the remaining portion of the device has not been shown in detail.

The initial position is shown in Figure 4a with the machine positioned above a layer of tissue 116 in which it is desired to form stitches. Suction is then applied to the slot 102 via the channel 104 to suck into the slot a double layer of tissue, as can be seen in Figure 4b. The depth and width of the slot 102 controls the amount of tissue which is sucked in. The modular design of this embodiment makes it possible to vary the amount of tissue

3

GB 2 165 559 A

3

sucked in, and hence vary the size of the stitches, simply by removing module B and replacing it by a module having a different thickness of depth of slot.

- 5 The needle 105 is then forced forwards through the double layer of tissue, as shown in Figure 4c. The needle carries with it a loop of a thread 109. The needle passes in front of the upwardly extending tip portions of both of the wires 151, as viewed
10 in Figure 4c. The control wire 115 is then pushed leftwards, as shown in Figure 4c, to cause the U-shaped member 111 to pivot anti-clockwise and thus to cause the wires 151 to catch the loop of thread carried by the eye of the needle 105. The
15 needle 105 is then withdrawn rightwards whilst the U-shaped member is rotated fully anti-clockwise carrying the thread upwards into the compartment 110. This is shown in Figure 4d. This last action forms the thread into a large diameter loop. This
20 results from the fact that the wires 151 diverge from one another as considered in a direction running leftwardly from their tips.

The suction applied to the slot 102 is then released and the double layer of tissue, with the
25 thread 109 passing through it, leaves the slot. This is also shown in Figure 4d.

- The machine is then moved with respect to the tissue in any direction to the right of a plane drawn perpendicular to the plane of the paper and passing through the machine. Thus, the machine could be moved rightwardly in a direction parallel to its
30 length, or at any angle less than 90° with respect to the aforesaid direction. The step shown in Figure 4e is then carried out, that is to say, suction is re-applied and the needle caused to pass through a
35 double layer of tissue at a different point to that where the needle passed through the tissue in step 4c. As can be seen in Figure 4e, the forward end of the needle passes through the loop of thread already held by the U-shaped member 111, carrying
40 a second loop of thread with it. Once the needle has placed this second loop through the first loop, the U-shaped member is pivoted clockwise, as shown in Figure 4f. The wires 151, being resilient,
45 are forced apart by the needle and thus pass one on either side of the needle as the U-shaped member 111 travels to the position shown in Figure 4f, in which it is below the needle. In so doing the wires 151 drop the first loop onto the second loop.

- 50 The member 111 is then pivoted anti-clockwise, as shown in Figure 4g, so as to catch the second loop carried by the eye of the needle. This is shown in Figure 4g. Both wires 151 at this stage lie against the needle 102 and between the needle 102
55 and the adjacent portion of the thread 109.

- As shown in Figure 4h, the needle 102 is then withdrawn rightwardly and the member 112 is pivoted further in an anti-clockwise direction, carrying the second loop upwards with it. As also
60 shown in Figure 4h, the suction is then released to allow the tissue to leave the slot 102.

The above procedure is repeated as many times as are necessary in order to produce the desired number of stitches.

- 65 Various modifications may be made to the em-

bodiments described above. One of these is that the machine can be provided with a plurality of slots 2 into each of which a double layer of tissue may be sucked. A single needle can then pass
70 through each of these double layers of tissue, thus making a plurality of stitches in a single operation. Also, it should be understood that the stitch forming part of the machine could be modified to correspond to that of any one of a number of
75 conventional sewing machines. For example, the stitching mechanism could be one which uses two threads, rather than one as in the illustrated embodiments.

- As mentioned above, the module A is preferably transparent. This is to make it easier for the operator to see, and hence control the operation of the machine. Visibility may further be improved, both in the embodiment of Figures 3 and 4 and in the embodiment of Figure 1, by positioning a mirror in the slot 102 (or slot 2) at 45° to the longitudinal axis of the machine. By way of example this is shown diagrammatically as 153 in Figure 3b. This enables the user to see the double layer of tissue sucked into the slot 2. A still further improvement can be achieved by extending the endoscope optics right up to the slot 102 (or 2).

- Some of the principles utilised in the above sewing machines can be applied with similar effect to the construction of a stapling machine which can also be used in a surgical environment. An embodiment of such a stapling machine is shown in figures 5a to 5c, which show successive steps in its operation.

- The stapling machine comprises a body 200 which, if desired, may be of modular construction. The body is preferably wholly or partially of a transparent material. The body defines a cavity 202 into which tissue 126 may be sucked by suction applied through a suction channel 204. Before use,
100 the cavity 202 is pre-loaded with a staple 209. The body also contains a second channel 203 through which extends a wire 206 carrying a piston 205 at its end. The cavity 202 has, in one wall thereof, an anvil plate 260, for a purpose which is described below.
105

- In the starting condition shown in Figure 5a, the staple 209 comprises four consecutive rectilinear sections, namely a first upwardly extending section, a second horizontally extending section, a third diagonally downwardly extending section, and a fourth section, which is parallel to the second section, and has its free end directed towards the first section. In the condition shown in Figure 5a suction has been applied to the channel 204 to suck into it a double layer of tissue 216. As shown in Figure 5b the next step is for the piston 205 to be moved leftwardly by means of the wire 206, thus driving the fourth sections of the staple through the double layer of tissue so that its tip comes into contact with the anvil 260, and simultaneously deforming the remaining sections of the staple. As shown in Figure 5c, further leftward movement of the piston 206 causes the tip of the staple to ride along the anvil 206, thus twisting it around the first section of the staple and locking
120
125
130

4 GB 2 165 559 A

4

the staple so that it exerts a compressive force of the tissue held by it. The illustrated embodiment shows only a single staple. However, the machine may carry a plurality of staples connected side by side as in the case of staples used, for example, in stationary applications. In this case, the row of staples is biased, for example, by a spring exerting a force perpendicular to the plane of the paper as viewed in figure 5, a stop being provided to retain the row of staples in the correct position against the biasing force. Figures 6a to 6f show, in part, a further embodiment of a sewing machine according to the present invention. The construction of this embodiment will become apparent from the following description of how it operates. The machine comprises two needles 20 and 30. Before the stage shown in Figure 6a, the needles are withdrawn such that their tips are separated by about 5mm. Then, as shown in Figure 6a, the first needle 20 is passed obliquely through the tissue 16, as indicated by the arrow. The needle 20 has a pair of opposed barbs 21 separated by a slot 22. The slot 22 provides access to an opening 23. A loop of thread 24 is carried forwardly by the needle. The tissue 16 is held in place by suction applied to a tube 25, the distal end of which carries the sewing machine of which the needle 20 forms a part. Only the end of the tube 25 is visible in the figures. The proximal end of the needle 20 is guided for rectilinear movement in a bush (not shown).

As shown in Figure 6b, once the needle 20 has been passed through the tissue to the full extent which is required an identical needle 30 is inserted through the tissue at a location remote from that at which the needle 20 passed through the tissue. The needle 30 is angled oppositely to the needle 20 so that, as shown in Figure 6b, its path of travel intersects that of the needle 20. At this stage the needle 30 carries no thread. Furthermore, the needle 30 is rotated by 90° about its longitudinal axis compared to the needle 20. The needle 30 has a slot 32, corresponding to slot 22 of needle 20, and barbs 31, corresponding to barbs 21 of needle 20. As shown in Figure 6b, the needle 30 passes between the needle 20 and the loop of thread 24 carried by the needle 20. To assist in this the needle 20 is provided with a depression 26 which is obscured in Figure 6 but which can be seen in Figure 6c.

In the position illustrated in Figure 6b, the slot 32 is located immediately below the thread 24. This causes the thread 24 to pass through the slot 32 and thus causes it to be caught by the needle 30.

As shown in Figure 6c, the needle 30 is then partially withdrawn, and as it does so it pulls the loop of thread 24 with it. As shown in Figure 6d, when the needle 20 is then partially withdrawn the thread 24 is freed from the needle 20 and held only by the needle 30. Further withdrawal of both needles 20 and 30 to a position where both pass out of the tissue 16 causes the situation to be reached which is shown in Figure 6e where a stitch has been formed.

Each of the needles 20 and 30 is then rotated by 90° about its own axis, so that needle 20 assumes

the orientation and function which was previously that of needle 30 and needle 30 assumes the orientation and function which was previously that of needle 20. The above described process is then repeated with the functions of the needles 20 and 30 interchanged. This procedure is continued as many times as are necessary to produce the required number of stitches.

The use of an endoscopic sewing machine according to the present invention gives rise to a requirement for a suitable means for securing knots and cutting thread. Secure knots are essential for surgery, and tying knots and cutting thread by remote control in confined spaces, as is necessary in conjunction with the use of the endoscopic sewing machines described above, imposes special requirements. Some ways of satisfying these requirements are therefore mentioned below.

One method of tying a knot is as follows. A washer having a central hole, the diameter of which is a clearance fit on the thread to be fastened is fed onto the thread. The thread is tied as a half-hitch around a pin pressed through the two walls of the end of a strong but flexible catheter tube. By holding the tail of the thread and pushing on the tube the half-hitch and washer in front of it may be run forward. When the desired position has been reached, the pin is removed remotely by pulling on a wire to which it is attached and which runs along the outside of the catheter. In another method of fastening the thread, a plastic washer is run over the thread down the endoscope channel. Plastic is preferred to metal because it is resistant to acid digestion. A compressible tapered sleeve is passed over the thread and a rammer bears down on the sleeve, distorting it tightly over the thread and against the washer while pull is exerted on the thread. Yet another method of fastening the thread uses a Z-shaped plastic strip having holes for the thread in the three limbs of the Z-shape. There is a V-shaped slit cut in the proximal hole. The thread is run through all the three holes of the Z-shaped strip which is pushed through the endoscope channel. A pushing device compresses and folds the Z-shaped strip like a flattened concertina against the tissue. This tightens on the thread forcing it into the narrow V-shaped slit which holds the thread securely.

Figure 7 shows a thread guillotine for endoscopic use. This comprises a crooked leg 40 with a slit 41 cut centrally along its length at one end thereof. The leg 40 is formed on the end of a metal tube 42 which is pressed over the end of a small diameter plastic catheter tube 43. A knife blade 44 is held in a piston 45 which is free to move axially in the bore of the tube 43. A wire 46 attached to the piston 45 and running through the bore of the tube 43 controls the movement of the blade when pushed forward. The blade 44 passes through the slot 41 in the crooked leg, thereby acting as a guillotine to sever the thread 47.

Finally, mention may be made of a suction over-tube to facilitate sewing down an endoscope by means of a machine according to the present invention, or indeed by some other means. The ov-

5

GB 2 165 559 A

5

ertube envisaged is a transparent flexible tube which fits loosely over the endoscope. An air-tight seal is made with an elastic sleeve between the overtube and the endoscope. A hole of specific dimensions is cut in the extreme end or in the side of the overtube distally. Air is sucked from the overtube such that tissue to be sewed protrudes into the overtube where it is held in a conformation which enables the tissue to be readily transfixed by a threaded needle.

It is to be understood that the various devices described above as being ancillary to the sewing machine according to the present invention are believed to be novel in their own right and form independent aspects of the present invention.

CLAIMS

1. A sewing machine for forming stitches in a substrate, comprising thread-carrying means for passing a thread into the substrate from one side thereof at a first location and for withdrawing the thread from the substrate at a second location spaced from the first location, the said means being remotely operable solely from the said one side of the substrate.

2. A machine according to claim 1, comprising means defining a slot open towards the substrate, and means for drawing a double layer of the substrate into the slot, the thread-carrying means being disposed for movement from a retracted position to an extended position, in which movement it carries a loop of the thread into and through the said double layer, and further comprising means for catching the said loop after it has been passed through the double layer of substrate and holding the said loop while the thread-carrying means is withdrawn to the retracted position.

3. A machine according to claim 2, wherein the catching means is movable from a catching position to a position in which the loop caught thereby is positioned so that subsequent movement of the thread-carrying means from said retracted position to said extended position carries a further loop of thread through the previously caught loop.

4. A machine according to claim 2 or 3, comprising a channel communicating with said slot for supplying suction thereto to effect the said drawing in of the double layer.

5. A machine according to claim 4, comprising a block having distal and proximal ends, the block defining a compartment adjacent the distal end housing the catching means, said slot being defined in the block on the proximal side of the compartment, said suction-supplying channel being defined in the block on the proximal side of the slot, a further channel being defined on the proximal side of the slot and communicating with the slot, said thread-carrying means being slidably received therein for movement between said retracted position, in which the thread-carrying means is substantially wholly within said further channel, and said extended position, in which the thread-carrying means extend across said slot into said compartment.

6. A machine according to claim 5, wherein control means for controlling the catching means extends through the suction-supplying channel and across said slot into said compartment to connect with the catching means.

7. A machine according to claim 6, wherein said control means comprises a flexible wire, and wherein the machine further comprises a further flexible wire for moving the thread-carrying means between the retracted and extended positions.

8. A machine according to claim 6 or 7, wherein the catching means comprises a shoe resiliently mounted in the compartment for pivotal movement about an axis transverse to the length of the block, and a hook pivotally mounted at one end of the shoe and movable by said control means between a position in which the other end thereof is in contact with the shoe and a position in which there is no such contact.

9. A machine according to claim 6 or 7, wherein the catching means comprises a pair of arms defining a U, the U-shaped member being mounted in the compartment for pivotal movement about an axis transverse to the length of the block and a pair of resilient members each extending from a respective one of said arms, the resilient members converging towards one another adjacent the outward ends thereof, the U-shaped member being movable by said control means between an outward position in which, when the thread-carrying means is in its extended position both resilient members are closely adjacent the thread-carrying means on the same side thereof, and an inward position in which the resilient members are located inwardly of the thread-carrying means.

10. A machine according to any of claims 5 to 9, wherein the block is formed of a plurality of disconnectible modules located face to face, one of said modules being a module defining said slot.

11. A machine according to any of claims 5 to 10, wherein proximally of the slot the block is transparent.

12. A machine according to any of claims 5 to 11, further comprising mirror located in the said slot and angled with respect to a line extending between the proximal and distal ends of the block.

13. A machine according to claim 1, comprising means for holding said substrate, first and second needles guided for movement along the axis thereof and arranged so that said axes intersect at a point located away from said substrate on the opposite side thereof to said one side thereof, means on each needle for holding a loop of thread and for catching the loop of thread held by the other needle.

14. A machine according to claim 13, wherein the thread-holding and thread-catching means comprises an opening formed in the needle and a slot communicating with said opening and providing access thereto.

15. A machine according to claim 14, wherein each needle is rotatable about the axis thereof between a thread-transporting position and a thread-releasing position at 90° thereto in which the other needle can remove the thread transported thereto.

16. A machine according to any preceding claim, mounted on an end of an endoscope.

17. A stapling machine for inserting a staple in a substrate, comprising means defining a slot open
5 towards the substrate, the slot being configured to receive at least one staple having opposite end portions which are spaced from one another to define a gap therebetween, means for drawing a double layer of the substrate into the slot and
10 through said gap, and means for forcing one of said staple end portions through the double layer of substrate.

18. A machine according to claim 17, comprising an anvil disposed in the slot adjacent the other
15 of said staple end portions and arranged so that when said one staple end portion is driven through the double layer of substrate it strikes the anvil and is deformed thereby into a position closely adjacent said other staple end portion.

20 19. A machine according to claim 17 or 18, comprising a channel communicating with said slot for supplying suction thereto to effect said drawing in of the double layer.

20. A machine according to any of claims 17 to
25 19, mounted on an end of an endoscope.

21. A guillotine for use in severing a thread, comprising a tube, a leg extending from one end of the tube and having an inwardly directed end portion with longitudinal slot formed therein, and a
30 blade mounted on mounting means which are arranged to move longitudinally within the tube between a forward portion in which the blade passes through said longitudinal slot and rearward position in which the blade is spaced from the longitudinal slot.
35

22. A guillotine according to claim 21, comprising a catheter tube, the said mounting means being arranged to slide within the catheter tube and the tube which has the said leg being fixedly
40 mounted on the exterior of the catheter tube.